

Project:
Quantity:
Notes:
Type:

General

Warranty	3 Year Full Replacement
Lens Construction	UV Stabilized Polycarbonate
Housing	PVDV Coated Aluminum
Water Proof Rating	IP68
Operating Temperature	-13°F to 158°F
Dimensions (in)	Ø 5.67" x 3.56"
Weight (lbs)	1.54



	Solar Module Size	1.85" x 1.85"
	Solar Maximum Output Power	0.267W
	Solar Operating Current	54mA
	Solar Voltage	4.95V
	LED Size	Ø5 LED
	LED Current	20mA per each
	LED Operating Current	8mA (4PCS)
	LED Voltage	3V
	LED Wattage	0.024W(4PCS)
	LED Quantities	3 pcs / 6 pcs
	Lithium Ion Battery	3.7V, 2,600mA

Certification	Test Method
Compressive Load: 69,691 lbf	ASTM C 67:06
	IEC 60529:2001

Performance

Charge Time	3 hrs/8 hrs Cloudy
Operating Time	16+ Hours
Cycles (Days)	100,000
Expected Life	10+ yrs

How to specify:

Model	Function	Color	Lux
SWL-135	S-Steady	R-Red	333
	FF-Fast Flash	G-Green	515.5
	SF-Slow Flash	B-Blue	83.55
		Y-Yellow	272.5
		W-White	780

Example: SWL-135SWW

SWL-135, Steady, White Bi-Direction

AMERICAN COMBAT VETERAN OWNED COMPANY

